



Transfer unit Oil can be easily transferred from an oil drum to the machine reservoir or vice versa.

Complete portability unit can be wheeled readily from place to place. Low cost maintenance. The CADILLAC ENGINEERING WORKS provides periodic 10-15-25 micron filtration of hydraulic system as required and pays for itself through longer hydraulic system life.

No down time.

Oil can be recirculated and filtered without shutting down your machine.

Plug in operation.

1440 RPM 230 VOLT 50 Cycle motor with on/off switch drives pump on the CADILLAC ENGINEERING WORKS.

It may be plugged into any electrical outlet using the meter cord provided.

General Usage :

The CADILLAC ENGINEERING WORKS is an integral unit consisting of a 10-15-25 micron filter, pump electric motor and hand truck. It is easy to move from one location to another provides simple, compact storage when the unit is not in use. CADILLAC ENGINEERING WORKS can also provide tailormade "Porta Filter & oil filtration plant" as per customer's requirement. The standard unit is designed for use with either petroleum or water glycol fluid Units can be provided for systems utilizing synthetic or water in oil emulsions.

CONTACT US AT:



CADILLAC ENGINEERING WORKS.

69B, SANTOSHPUR AVENUE.

KOLKATA- 700 075.

PHONE: 033 2416 2535 / 2536 • TELE FAX: 91 (033) 2416 25 36.

Email: sales@cadillacfilter.com / cadillacengg@rediffmail.com

Website : www.cadillacfilter.com